



9837 Pioneer Blvd.
 Santa Fe Springs, CA 90670
 Ph: 562-463-9160 Fax: 562-463-9170
 www.allstarcable.com

Specification Sheet

Part# LUT-CBL522-PLEN

Description: 22 AWG, 5 conductor solid bare copper with FEP insulation, aluminum/mylar shielded with a stranded tinned copper drain wire and an overall FEP jacket. Sensor cable for Lutron Eco Systems

1. **Conductor**
 - 1.1. AWG & Stranding: 22 AWG Solid
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 5 Conductors
2. **Insulation**
 - 2.1. Material: Fluorinated Ethylene Propylene
 - 2.2. Wall Thickness: 0.009"
 - 2.3. Color Code: Black, Red, White, Yellow & Blue
3. **Assembly**
 - 3.1. Cable Lay Length: 2.00" LHL (6 Tw/Ft)
 - 3.2. Cable Shield: Aluminum/Mylar Tape - 100% coverage
 - 3.3. Cable Drain Wire: 22 AWG Solid Tinned Copper
4. **Jacket**
 - 4.1. Material: Fluorinated Ethylene Propylene
 - 4.2. Wall Thickness: 0.012"
 - 4.3. Diameter: 0.144"
 - 4.4. Color: Natural
 - 4.5. Ripcord: Yes
 - 4.6. Weight: 24 Lbs/Mft
5. **Markings**
 - 5.1. Type: Cable permanently identified with marker tape under jacket
 - 5.2. Legend: AVALANCHE™ MFG FOR LUTRON ECO SYSTEM 22AWG 5C SHIELDED E171197 (UL) CMP C(UL)US OR (UL) CL3P 200°C FT-6 "ROHS"
 - 5.3. Footage markers: N/A
6. **Nominal Electrical Characteristics**
 - 6.1. DC Resistance: 16.5 Ω/Mft @ 20°C
 - 6.2. Impedance: 64 Ω
 - 6.3. Capacitance: 22.8 pF/ft
7. **Standards**
 - 7.1. Refer to NEC (NFPA 70) article 800 for installation guidelines
 - 7.2. UL listed as Type CL3P per UL Standard 13 or as type CMP c(UL)us 200°C FT-6 per UL Standard 444
 - 7.3. All materials used in the manufacture of this cable are RoHS compliant
 - 7.4. Recommended Operating Voltage: 300V
 - 7.5. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION